


Technical data sheet

Roll goods with pre filter F9



Similar to picture

Technical data:

Product	Filter roll with pre filter
Medium	Synthetic
Colour media	white / white
Dimension (width x length) [m]	1 x 1
Filter area [m ²]	1
Filter class	F9
Air velocity [m/s]	0,15
Initial pressure drop flat sheet tested approx. [Pa]	85
Average arrestance [%]	-
Average efficiency at 0.4 µm [%]	≥ 95
Discharged efficiency of media (0.4 µm) [%]	-
Maximum humidity resistance [%]	100
Labelling	Filter class, type test

Characteristics of test:

Classification	EN 779:2002
Fire protection	DIN 53438 - 3 (F1)
Pollutant tested	Oeko - Tex Standard 100 product class II (Products with skin contact)



Product Benefits:

- The roll goods is available in following versions: welded, sewn, endless pockets	- The filter media is compressed towards clean air side and takes full depth of fibrous web for dust absorption
- Shatter-proof synthetic fibres, environmentally safe	- Lacquer compatibility according to IPA-control

Note:

All information and illustrations are sole property of and are provided to the best of our company's knowledge. Yet our company does not take over any warranty for the completeness and/ or correctness and cannot be held liable for any damage occurring to the recipient through the use or through her or his trust in the completeness and/ or correctness of the information. The given data are mean values with tolerances due to normal production variations and do not release the recipient from own checks, investigations and test. Furthermore, all data serve as service description and shall not be interpreted as a warranty for composition or service life.